

IAU-214 and IAU-234

Image Auxiliary Unit with factory installed supply and load cables



PRODUCT OVERVIEW:

The IAU-214 and IAU-234 are auxiliary load control units used with an IMC-213 module. They slide together with the IMC-213 to create a single control platform. These units are designed to operate a single speed pump, variable speed pump or a variable speed blower load.

FEATURES / BENEFITS

- On/off control for single speed loads, or
- Variable phase angle power control for variable speed loads
- Massage mode that cycles through the power range
- Diagnostics through bi-directional communication with the smart display
- Up to four IAU-214 in a single system to create custom configurations
- Intra-module communication through infrared link reduces cable requirements
- Printed circuit board is conformal coated for protection against corrosion
- Physical box dimensions approximately: 6.80" x 2.15" x 3.45" (170mm x 55mm x 88mm)

CONFIGURATIONS

Part Number	Description
IAU-214-01-01-01	Auxiliary unit 120V Hardwire/Hardwire
IAU-214-01-02-01	Auxiliary unit 120V NEMA/Hardwire
IAU-214-01-03-01	Auxiliary unit 120V NEMA/NEMA
IAU-234-01-01-01	Auxiliary unit 220V Hardwire/Hardwire



150 Rosamond Street, Carleton Place, Ontario, Canada K7C 1V2
Phone: 613-257-7356 Fax: 613-257-1840
An ISO 9001:2000 Registered Company